

PSAIL® T309 also known as triphenyl thiophosphate, is an ashless extreme pressure and anti-wear agent that can be widely used as an anti-wear additive in various oil products such as anti-wear hydraulic oil, oil film bearing oil, hydraulic transmission oil, and turbine oil. It exhibits excellent anti-wear properties, oxidation resistance, thermal stability, and color stability.

CHEMICAL COMPOSITION

Triphenyl thiophosphate (T309)

CAS No.: 597-82-0

TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance	White or yellowish crystal	Visual inspection
Purity, %	99.8	LC method
Phenol content, %	59.2	GC method
Meting point, °C	52.0	GB/T 617
Flash point open cup, °C	>200.0	GB/T 3536
Sulfur content, %	9.3	SH/T 0303
Phosphorus content, %	8.9	SH/T 0296

Note: The above analytical data are not specifications.

PERFORMANCE CHARACTERISTICS

- Good solubility and easy mixing
- Good wear resistance, oxygen resistance, thermal stability and color stability
- Combined with **PSAIL® 3490**, the effect is better

APPLICATION

- Industrial lubricating oils
- Greases

USAGE METHOD

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended treat level: 0.5-3.0%

RELATIVE PRODUCTS

- IRGALUBE TPPT, T309

PACKAGING AND STORAGE

Packaging	25kg/bag (Net weight)
Storage conditions	Store in a cool, dry, well-ventilated warehouse

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on **PSAIL® T309**.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.