


CSAIL[®] 3000 is a triazole derivative, it is a liquid, oil soluble, metal deactivator. It offers superior protection for yellow metals against corrosion, ensuring that these crucial components function effectively and have a prolonged service life. It stands out in its ability to perform with high efficiency at low concentration levels, combining excellent oil solubility and a synergistic effect with antioxidants.

CHEMICAL COMPOSITION



Triazole derivatives

CAS No.: 91273-04-0

TYPICAL PROPERTIES

Test Item	Typical Data	Method
Appearance	Light yellow to yellow clear liquid	Visual inspection
Density at 20°C, g/cm ³	0.91	GB/T 1884
Viscosity at 40°C, mm ² /s	33.0	GB/T 265
Flash point open cup, °C	≥130.0	GB/T 3536
Water content, %	0.18	GB/T 11133
Nitrogen content, %	17.3	NB/SH/T 0656

Note: The above analytical data are not specifications.

PERFORMANCE CHARACTERISTICS

- Protects yellow metals from corrosion
- Excellent oil solubility, excellent synergistic effect with antioxidants
- High efficiency protection at low concentration
- Contains no diluents

APPLICATION

- Various lubricating oils
- Greases

USAGE METHOD

- Added to the formulation directly and compatibility needs to be tested before adding
- Recommended treat level:
 - Industrial lubricants 200-1000 ppm
 - Transformer oils 10-50 ppm

RELATIVE PRODUCTS

- IRGAMET 30, CUVAN 313

PACKAGING AND STORAGE

Packaging	50kg plastic drum or 180kg steel drum (Net weight)
Storage conditions	Store in a cool, dry, well-ventilated warehouse

HANDLING INFORMATION

Avoid contact with skin, eyes and clothing. Operate in accordance with good industrial health and safety practices. Please refer to material safety data sheet (MSDS) for additional handling information on **CSAIL®3000**.

Luoyang Pacific United Petrochemical Co., Ltd. (UNPChemicals) hopes that the information provided will be helpful to you. The information provided in this document has been prepared by technicians and is true and accurate as of the date of this document. However, please note that the conditions of your use and application of our products, technical assistance and information (whether orally, in writing or through product evaluation), including any suggested formulations and recommendations, are outside our control. UNPChemicals makes no representations, warranties or warranties (whether express, implied, statutory or otherwise), or implied warranties as to the completeness, accuracy or timeliness of any information. It is therefore important that you test our products, technical assistance and information, including how they are packaged, to determine their performance, efficacy and safety. You are solely responsible for the performance, efficacy and safety of any products you produce. UNPChemicals assumes no liability and you bear all risks and liabilities for any use or handling of any material. Nothing in this document should be interpreted as suggesting the use of any product that conflicts with the patent covering any material or its use. No license is implied or granted under the claims of any patent. We will provide consistent quality products within our sales conditions.